



Asbestos Testing in Building Material: Fibre Cement

If the sample material looks like a sprayed finish, particularly if it is insulating material on pipework, boilers or ceilings, do not sample yourself!

Disturbing loose fibrous insulation material that contains asbestos is extremely dangerous. It is highly recommended that sampling is carried out by qualified individuals.

However, if you are collecting a sample yourself, the instructions below provide minimum precautions. If in doubt or for further information, we highly recommend that you contact us.

- ✔ Dampen or wet the material.
- ✔ Before using pliers or any other available tool, place a baby-wipe to protect the inside edges of the tool - If the inside of the pliers is "ribbed" or textured, this precaution helps limit the possibility of parts of the sample getting stuck in these textured areas.
- ✔ Break off a small thumbnail sized sample.
- ✔ Place the sample into a sealable polythene bag, such as a sandwich bag.
- ✔ Place the bagged sample into another sealable bag.
- ✔ Attach a label to the bag that identifies the sample type and sample location. An example of sample type is fibre cement and sample locations might include ceiling tiles or fireboards.
- ✔ Include **your name**, address, email address and **contact number** with your sample being tested for asbestos.
- ✔ Seal the exposed edge of the sample being tested for asbestos with duct tape or paint to avoid fibre release.
- ✔ Clean any tools used with a wet paper towel or baby-wipes and place in a separate bag to the sampled material – Upon receipt, our team will organise the safe disposal of discarded tools used in the sample collection.



Forward your well packaged sample to one of our **Envirolab NATA accredited** labs:

Envirolab Services
12 Ashley
Chatswood NSW 2067

or

MPL Laboratories
16-18 Hayden Court
Myaree WA 6154

With your sample, include your payment of \$110 including GST for one sample*

We accept Visa, MasterCard, direct deposit or cheque payments. PLEASE MAKE CHEQUES PAYABLE TO ENVIROLAB SERVICES.

* Discount available for combining multiple samples in a test job.

Results will be reported within 2 working days.

Ask us about the **fastest turnaround of 2-3 hours** for results. A surcharge applies for faster turnarounds. You will be given a certificate that identifies whether asbestos is present and the type of asbestos present in the sample.

In most cases, asbestos containing materials can safely be left in place, as there will be little or no risk of fibre release.

For further information contact our laboratories



1300 424 344



envirolab.com.au

Great Science. Great Service.